







PROJECT ROUTE CLOSURE

# LEGEND

-  Traffic Sign
-  Type III Barricade (Type 'A' Low Intensity Flashing Warning Lights Required for Nighttime Use)
-  Orange Plastic Safety Fence
-  Type 'A' Low Intensity Flashing Warning Light
-  Work area

## GENERAL NOTES

1. This layout illustrates traffic control necessary to close the project route.
2. Road closures will be measured and paid for according to Section 2518 of the Standard Specifications.
3. When distance "A" is less than 500 feet, the barricade should be placed in the middle of the traffic lane approaching the work area. In this case, Type 'A' Flashing Warning Lights shall be visible to both directions of traffic. The barricade may be omitted if the distance to the work area is less than 250 feet.
4. If the intersection is the beginning of a marked detour, these two signs and barricade will become the responsibility of the Contracting Authority and may be modified by the Contracting Authority to fit detour signing.

 <b>Iowa Department of Transportation</b> <b>Project Development Division</b>	
<b>STANDARD ROAD PLAN RS-27</b>	
REVISION: Delete notes 2 and 3. Add new note 2.	REVISION NO. 1
APPROVED BY DESIGN METHODS ENGINEER <i>David P. Keith</i> 06-23-97	REVISION DATE 10-28-97
TRAFFIC CONTROL LAYOUT FOR TEMPORARY ROAD CLOSURES AT BRIDGES AND SPOT LOCATIONS ( RURAL AREAS )	